

Brake Cleaner

Revision: 2/03/2016

Page 1 from 1

Technical data

Basis	Solventbased mixture
Consistency	Liquid
Density	Ca. 0,69 g/ml
Viscosity (Brookfield)	1 mPa.s
Flashpoint	< 20 °C
Acidity level (text)	Neutral
Solubility in water	Not soluble
Volatile Organic Compounds (VOC)	97 %
Propellant gas	CO ₂ (carbon dioxide)
Application temperature	5 °C → 35 °C

(*) these values may vary depending on environmental factors such as temperature, moisture, and type of substrates.

Product description

Brake Cleaner is a powerful, fast-drying cleaner for brake and clutch parts.

Properties

- Cleans and degreases
- Leaves no residue
- Fast drying
- Does not corrode metals
- Prevents squeaking sounds
- Aerosol can be used in any angle (360°)

Applications

- Removes excess brake fluid, excess oil, dirt, etc. quickly.
- Prevents squeaking brakes and clutch slipping.
- Easy to apply from all angles and does not corrode metals.

Packaging

Colour: transparent

Packaging: 400 ml aerosol

Shelf life

3 years in unopened packaging in a dry and cool environment at temperatures between +5°C and +25°C.

Substrates

Nature: clean, free of dust and grease.

All types of metals and plastics.

Application method

Application method: Shake can well before use. Spray sufficient product on the parts to be cleaned and let it work for a few seconds. If necessary, wipe clean with an absorbing cloth. In case of extensive carbon contamination, repeat the procedure. Do not use on rubber, plastics or painted parts. Test for adverse effects on the surface in advance. Make sure there is sufficient ventilation when using the product.

Health- and Safety Recommendations

Use only in well-ventilated areas. In case of contact with eyes, wash immediately with plenty of water.

Liability

The content of this technical data sheet is the result of tests, monitoring and experience. It is general in nature and does not constitute any liability. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application.

Remark: This technical data sheet replaces all previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions beyond our control, no liability under this publication are accepted. In every case it is recommended to carry out preliminary experiments. Soudal reserves the right to modify products without prior notice.