

## Soudal SA Fill & Fix Foam

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name : Soudal SA Fill & Fix Foam  
 Registration number REACH : Not applicable (mixture)  
 Product type REACH : Mixture

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant identified uses  
 polyurethane

1.2.2 Uses advised against  
 No uses advised against known

#### 1.3. Details of the supplier of the safety data sheet

##### Supplier of the safety data sheet

SODAL N.V.  
 Everdongenlaan 18-20  
 B-2300 Turnhout  
 ☎ +32 14 42 42 31  
 ☐ +32 14 42 65 14  
 msds@soudal.com

##### Manufacturer of the product

SODAL N.V.  
 Everdongenlaan 18-20  
 B-2300 Turnhout  
 ☎ +32 14 42 42 31  
 ☐ +32 14 42 65 14  
 msds@soudal.com

#### 1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch):  
 +32 14 58 45 45 (BIG)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

Class	Category	Hazard statements
Aerosol	category 1	H222: Extremely flammable aerosol.
Aerosol	category 1	H229: Pressurised container: May burst if heated.
Carc.	category 2	H351: Suspected of causing cancer.
Lact.	-	H362: May cause harm to breast-fed children.
Acute Tox.	category 4	H332: Harmful if inhaled.
STOT RE	category 2	H373: May cause damage to organs through prolonged or repeated exposure if inhaled.
Eye Irrit.	category 2	H319: Causes serious eye irritation.
STOT SE	category 3	H335: May cause respiratory irritation.
Skin Irrit.	category 2	H315: Causes skin irritation.
Resp. Sens.	category 1	H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin Sens.	category 1	H317: May cause an allergic skin reaction.
Aquatic Chronic	category 4	H413: May cause long lasting harmful effects to aquatic life.

#### 2.2. Label elements



# Soudal SA Fill & Fix Foam

Contains: polymethylene polyphenyl isocyanate; alkanes, C14-17, chloro.

## Signal word

Danger

## H-statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H351	Suspected of causing cancer.
H362	May cause harm to breast-fed children.
H332	Harmful if inhaled.
H373	May cause damage to organs through prolonged or repeated exposure if inhaled.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H315	Causes skin irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317	May cause an allergic skin reaction.
H413	May cause long lasting harmful effects to aquatic life.

## P-statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P308 + P313	IF exposed or concerned: Get medical advice/attention.
P405	Store locked up.
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122°F.
P501	Dispose of contents/container in accordance with local/regional/national/international regulation.

## Supplemental information

- Persons already sensitised to diisocyanates may develop allergic reactions when using this product.
- Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.
- This product should not be used unless a power assisted filtering device incorporating full face mask (according to standard EN 12942) is used.

## 2.3. Other hazards

Gas/vapour spreads at floor level: ignition hazard

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name REACH Registration No	CAS No EC No	Conc. (C)	Classification according to CLP	Note	Remark
propane 01-2119486944-21	74-98-6 200-827-9	C>1%	Flam. Gas 1; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)	Propellant
dimethyl ether 01-2119472128-37	115-10-6 204-065-8	C>1%	Flam. Gas 1; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)	Propellant
polymethylene polyphenyl isocyanate	9016-87-9	5%<C<25%	Carc. 2; H351 Acute Tox. 4; H332 STOT RE 2; H373 Eye Irrit. 2; H319 STOT SE 3; H335 Skin Irrit. 2; H315 Resp. Sens. 1; H334 Skin Sens. 1; H317	(1)(2)(8)(10)	Constituent
isobutane 01-2119485395-27	75-28-5 200-857-2	C>1%	Flam. Gas 1; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)	Propellant
(1,3-butadiene, conc<0.1%)					
alkanes, C14-17, chloro 01-2119519269-33	85535-85-9 287-477-0	1%<C<20%	Lact. ; H362 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	(1)(2)(8)(10)	Constituent

Publication date: 2017-06-02

# Soudal SA Fill & Fix Foam

- (1) For H-statements in full: see heading 16  
(2) Substance with a Community workplace exposure limit  
(8) Specific concentration limits, see heading 16  
(10) Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General:

GENERAL: Check the vital functions. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim conscious with laboured breathing: half-seated. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Prevent cooling by covering the victim (no warming up). Keep watching the victim. Give psychological aid. Keep the victim calm, avoid physical strain. Depending on the victim's condition: doctor/hospital.

#### After inhalation:

Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.

#### After skin contact:

Wash immediately with lots of water. Take victim to a doctor if irritation persists.

#### After eye contact:

Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Do not apply neutralizing agents. Take victim to an ophthalmologist if irritation persists.

#### After ingestion:

Rinse mouth with water. Immediately after ingestion: give lots of water to drink. Do not induce vomiting. Consult a doctor/medical service if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

#### 4.2.1 Acute symptoms

##### After inhalation:

Dry/sore throat. Coughing. Irritation of the respiratory tract. Irritation of the nasal mucous membranes. Runny nose. FOLLOWING SYMPTOMS MAY APPEAR LATER: Possible inflammation of the respiratory tract. Risk of lung oedema. Respiratory difficulties.

##### After skin contact:

Tingling/irritation of the skin.

##### After eye contact:

Irritation of the eye tissue. Lacrimation.

##### After ingestion:

Not applicable.

#### 4.2.2 Delayed symptoms

No effects known.

### 4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### 5.1.1 Suitable extinguishing media

Small fire: Quick-acting ABC powder extinguisher, Quick-acting BC powder extinguisher.

#### 5.1.2 Unsuitable extinguishing media

Small fire: Quick-acting CO2 extinguisher, Water (water can be used to control jet flame), Foam.

Major fire: Water (water can be used to control jet flame), Foam.

### 5.2. Special hazards arising from the substance or mixture

On burning: release of toxic and corrosive gases/vapours (nitrous vapours, hydrogen chloride, carbon monoxide - carbon dioxide). Pressurised container: May burst if heated. May polymerize on exposure to temperature rise. On heating: release of toxic/combustible gases/vapours (hydrogen cyanide).

### 5.3. Advice for firefighters

#### 5.3.1 Instructions:

If exposed to fire cool the closed containers by spraying with water. Physical explosion risk: extinguish/cool from behind cover. Do not move the load if exposed to heat. After cooling: persistent risk of physical explosion. Dilute toxic gases with water spray. Take account of toxic/corrosive precipitation water.

#### 5.3.2 Special protective equipment for fire-fighters:

Gloves. Protective goggles. Head/neck protection. Protective clothing. Heat/fire exposure: compressed air/oxygen apparatus.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Stop engines and no smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment.

#### 6.1.1 Protective equipment for non-emergency personnel

See heading 8.2

Publication date: 2017-06-02

# Soudal SA Fill & Fix Foam

## 6.1.2 Protective equipment for emergency responders

Gloves. Protective goggles. Head/neck protection. Protective clothing.

### Suitable protective clothing

See heading 8.2

## 6.2. Environmental precautions

Dam up the solid spill. Use appropriate containment to avoid environmental contamination.

## 6.3. Methods and material for containment and cleaning up

Allow product to solidify and remove it by mechanical means. Carefully collect the spill/leftovers. Clean (treat) contaminated surfaces with acetone. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

## 6.4. Reference to other sections

See heading 13.

## SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

### 7.1. Precautions for safe handling

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Observe very strict hygiene - avoid contact. Remove contaminated clothing immediately.

### 7.2. Conditions for safe storage, including any incompatibilities

#### 7.2.1 Safe storage requirements:

Storage temperature: < 50 °C. Store in a cool area. Keep out of direct sunlight. Store in a dry area. Ventilation at floor level. Fireproof storeroom. Unauthorized persons are not admitted. Meet the legal requirements. Max. storage time: 1 year(s).

#### 7.2.2 Keep away from:

Heat sources, ignition sources, (strong) acids, (strong) bases.

#### 7.2.3 Suitable packaging material:

Aerosol.

#### 7.2.4 Non suitable packaging material:

No data available

### 7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1 Occupational exposure

##### a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

#### EU

Dimethylether	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	1000 ppm
	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	1920 mg/m <sup>3</sup>

#### Belgium

Hydrocarbures aliphatiques sous forme gazeuse : (Alcanes C1-C4)	Time-weighted average exposure limit 8 h	1000 ppm
Oxyde de diméthyle	Time-weighted average exposure limit 8 h	1000 ppm
	Time-weighted average exposure limit 8 h	1920 mg/m <sup>3</sup>

#### The Netherlands

Dimethylether	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	496 ppm
	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	950 mg/m <sup>3</sup>
	Short time value (Public occupational exposure limit value)	783 ppm
	Short time value (Public occupational exposure limit value)	1500 mg/m <sup>3</sup>

#### France

Oxyde de diméthyle	Time-weighted average exposure limit 8 h (VRI: Valeur réglementaire indicative)	1000 ppm
--------------------	---	----------

Publication date: 2017-06-02

# Soudal SA Fill & Fix Foam

Oxyde de diméthyle	Time-weighted average exposure limit 8 h (VRI: Valeur réglementaire indicative)	1920 mg/m <sup>3</sup>
--------------------	---	------------------------

## Germany

Chloralkane, C14-17 (Chlorierte Paraffine C14-17)	Time-weighted average exposure limit 8 h (TRGS 900)	0.3 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	6 mg/m <sup>3</sup>
Dimethylether	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	1900 mg/m <sup>3</sup>
Isobutan	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	2400 mg/m <sup>3</sup>
pMDI (als MDI berechnet)	Time-weighted average exposure limit 8 h (TRGS 900)	0.05 mg/m <sup>3</sup>
Propan	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	1800 mg/m <sup>3</sup>

## UK

Dimethyl ether	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	400 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	766 mg/m <sup>3</sup>
	Short time value (Workplace exposure limit (EH40/2005))	500 ppm
	Short time value (Workplace exposure limit (EH40/2005))	958 mg/m <sup>3</sup>
Isocyanates, all (as -NCO) Except methyl isocyanate	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	0.02 mg/m <sup>3</sup>
	Short time value (Workplace exposure limit (EH40/2005))	0.07 mg/m <sup>3</sup>

## USA (TLV-ACGIH)

Butane, all isomers	Short time value (TLV - Adopted Value)	1000 ppm
---------------------	--	----------

### b) National biological limit values

If limit values are applicable and available these will be listed below.

#### 8.1.2 Sampling methods

Product name	Test	Number
Isocyanates	NIOSH	5521
Isocyanates	NIOSH	5522

#### 8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

#### 8.1.4 DNEL/PNEC values

##### DNEL/DMEL - Workers

alkanes, C14-17, chloro

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	6.7 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	47.9 mg/kg bw/day	

##### DNEL/DMEL - General population

alkanes, C14-17, chloro

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	2 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	28.75 mg/kg bw/day	
	Long-term systemic effects oral	0.58 mg/kg bw/day	

##### PNEC

alkanes, C14-17, chloro

Compartment	Value	Remark
Fresh water	1 µg/l	
Marine water	0.2 µg/l	
STP	80 mg/l	
Fresh water sediment	13 mg/kg sediment dw	
Marine water sediment	2.6 mg/kg sediment dw	
Soil	11.9 mg/kg soil dw	
Oral	10 mg/kg food	

#### 8.1.5 Control banding

If applicable and available it will be listed below.

## 8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

### 8.2.1 Appropriate engineering controls

Publication date: 2017-06-02

# Soudal SA Fill & Fix Foam

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Measure the concentration in the air regularly.

## 8.2.2 Individual protection measures, such as personal protective equipment

Observe very strict hygiene - avoid contact. Do not eat, drink or smoke during work.

### a) Respiratory protection:

Wear gas mask with filter type A if conc. in air > exposure limit.

### b) Hand protection:

Gloves.

Materials	Breakthrough time	Thickness
LDPE (Low Density Poly Ethylene)	> 10 minutes	0.025 mm

### c) Eye protection:

Protective goggles.

### d) Skin protection:

Head/neck protection. Protective clothing.

## 8.2.3 Environmental exposure controls:

See headings 6.2, 6.3 and 13

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical form	Aerosol
Odour	Characteristic odour
Odour threshold	No data available
Colour	Variable in colour, depending on the composition
Particle size	Not applicable
Explosion limits	No data available
Flammability	Extremely flammable aerosol.
Log Kow	Not applicable (mixture)
Dynamic viscosity	No data available
Kinematic viscosity	No data available
Melting point	No data available
Boiling point	No data available
Flash point	Not applicable
Evaporation rate	No data available
Relative vapour density	> 1
Vapour pressure	No data available
Solubility	Organic solvents ; soluble Water ; insoluble
Relative density	0.95 ; 20 °C
Decomposition temperature	No data available
Auto-ignition temperature	No data available
Explosive properties	No chemical group associated with explosive properties
Oxidising properties	No chemical group associated with oxidising properties
pH	No data available

### 9.2. Other information

Absolute density	946.8 kg/m <sup>3</sup> ; 20 °C
------------------	---------------------------------

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

May be ignited by sparks. Gas/vapour spreads at floor level: ignition hazard.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

May polymerize with many compounds e.g.: (strong) bases and amines. Reacts violently with (some) acids/bases.

### 10.4. Conditions to avoid

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks.

### 10.5. Incompatible materials

(strong) acids, (strong) bases.

Publication date: 2017-06-02

# Soudal SA Fill & Fix Foam

## 10.6. Hazardous decomposition products

On heating: release of toxic/combustible gases/vapours (hydrogen cyanide). On burning: release of toxic and corrosive gases/vapours (nitrous vapours, hydrogen chloride, carbon monoxide - carbon dioxide).

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### 11.1.1 Test results

#### Acute toxicity

##### Soudal SA Fill & Fix Foam

No (test)data on the mixture available

##### polymethylene polyphenyl isocyanate

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50		> 10000 mg/kg		Rat	Literature study	
Dermal	LD50		> 5000 mg/kg		Rabbit	Literature study	
Inhalation (vapours)	LD50		10 mg/l - 20 mg/l	4 h	Rat	Literature study	
Inhalation			category 4			Literature study	

##### alkanes, C14-17, chloro

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50		> 4000 mg/kg bw		Rat (male/female)	Experimental value	
Dermal	LD50		> 13500 mg/kg bw	24 h	Rabbit	Read-across	
Inhalation (vapours)	LC50		> 48.170 mg/l air	1 h	Rat	Read-across	

Classification of the mixture is based on the bridging principle

#### Conclusion

Harmful if inhaled.

Not classified as acute toxic if swallowed

Not classified as acute toxic in contact with skin

#### Corrosion/irritation

##### Soudal SA Fill & Fix Foam

No (test)data on the mixture available

##### polymethylene polyphenyl isocyanate

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Irritating; category 2					Literature study	
Skin	Irritating; category 2					Literature study	
Inhalation	Irritating; STOT SE cat.3					Literature study	

The liquid form can cause frostbites, typical for all liquefied gases

The liquid form can cause frostbites, typical for all liquefied gases

##### alkanes, C14-17, chloro

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Slightly irritating				Rabbit	Expert judgement	
Skin	Slightly irritating	OECD 404	4 h	24; 72 hours	Rabbit	Expert judgement	

Classification is based on the relevant ingredients

#### Conclusion

Causes skin irritation.

Causes serious eye irritation.

May cause respiratory irritation.

#### Respiratory or skin sensitisation

##### Soudal SA Fill & Fix Foam

No (test)data on the mixture available

Publication date: 2017-06-02



# Soudal SA Fill & Fix Foam

## polymethylene polyphenyl isocyanate

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Sensitizing; category 1					Literature study	
Inhalation	Sensitizing; category 1					Literature study	

The study on skin sensitisation does not need to be conducted as the substance is a gas

The study on skin sensitisation does not need to be conducted as the substance is a gas

## alkanes, C14-17, chloro

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Guinea pig maximisation test		48 hours	Guinea pig	Experimental value	

Classification is based on the relevant ingredients

### Conclusion

May cause an allergic skin reaction.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

### Specific target organ toxicity

#### Soudal SA Fill & Fix Foam

No (test)data on the mixture available

## polymethylene polyphenyl isocyanate

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Inhalation			STOT RE cat.2					Literature study

## alkanes, C14-17, chloro

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral (diet)	NOAEL	Equivalent to OECD 408	300 ppm		No effect	13 weeks (daily)	Rat (male/female)	Experimental value
Oral (diet)	NOAEL	Equivalent to OECD 408	23 mg/kg bw/day - 24.6 mg/kg bw/day		No effect	13 weeks (daily)	Rat (male/female)	Experimental value
Dermal								Data waiving
Inhalation								Data waiving

Classification is based on the relevant ingredients

### Conclusion

May cause damage to organs through prolonged or repeated exposure if inhaled.

Not classified as sub-chronically toxic in contact with skin

Not classified as sub-chronically toxic if swallowed

### Mutagenicity (in vitro)

#### Soudal SA Fill & Fix Foam

No (test)data on the mixture available

## alkanes, C14-17, chloro

Result	Method	Test substrate	Effect	Value determination
Negative with metabolic activation, negative without metabolic activation	OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value

### Mutagenicity (in vivo)

#### Soudal SA Fill & Fix Foam

No (test)data on the mixture available

## alkanes, C14-17, chloro

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative	Equivalent to OECD 475	5 day(s)	Rat (male)	Bone marrow	Experimental value
Negative	Equivalent to OECD 474		Mouse (male/female)	Bone marrow	Experimental value

Classification is based on the relevant ingredients

### Conclusion

Not classified for mutagenic or genotoxic toxicity

Publication date: 2017-06-02



# Soudal SA Fill & Fix Foam

## Carcinogenicity

### Soudal SA Fill & Fix Foam

No (test)data on the mixture available

#### polymethylene polyphenyl isocyanate

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Unknown			category 2					Literature study

#### alkanes, C14-17, chloro

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Oral	LOAEL	Equivalent to OECD 451	312 mg/kg bw/day	104 weeks (5 days/week)	Rat (male/female)	Carcinogenicity	Liver; kidney	Read-across
Oral	LOAEL	Equivalent to OECD 451	312 mg/kg bw/day	103 weeks (5 days/week)	Rat (male/female)	Carcinogenicity	Thyroid	Read-across

Classification is based on the relevant ingredients

### Conclusion

Suspected of causing cancer.

## Reproductive toxicity

### Soudal SA Fill & Fix Foam

No (test)data on the mixture available

#### alkanes, C14-17, chloro

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity	NOAEL	Equivalent to OECD 414	5000 mg/kg bw/day	14 days (gestation, daily)	Rat	No effect		Experimental value
Maternal toxicity	NOAEL	Equivalent to OECD 414	500 mg/kg bw/day	13 days (gestation, daily)	Rat	No effect		Experimental value
Effects on fertility	NOAEL (P)	OECD 421	100 mg/kg bw/day	9 week(s)	Rat (male)	No effect	Male reproductive organ	Experimental value
	NOAEL (P)	OECD 421	100 mg/kg bw/day	11 week(s) - 12 week(s)	Rat (female)	No effect	Female reproductive organ	Experimental value
Effects on lactation			May cause harm to breast-fed children.					Experimental value

Classification is based on the relevant ingredients

### Conclusion

May cause harm to breast-fed children.

Not classified for reprotoxic or developmental toxicity

## Toxicity other effects

### Soudal SA Fill & Fix Foam

No (test)data on the mixture available

#### alkanes, C14-17, chloro

Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
	Other		Skin	Skin dryness or cracking		Rat	Experimental value

## Chronic effects from short and long-term exposure

### Soudal SA Fill & Fix Foam

ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Feeling of weakness. Itching. Skin rash/inflammation. May stain the skin. Dry skin. Coughing. Possible inflammation of the respiratory tract. Respiratory difficulties.

Publication date: 2017-06-02

# Soudal SA Fill & Fix Foam

## SECTION 12: Ecological information

### 12.1. Toxicity

Soudal SA Fill & Fix Foam

No (test) data on the mixture available

polymethylene polyphenyl isocyanate

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity other aquatic organisms	LC50		> 1000 mg/l	96 h				Literature study
Toxicity aquatic micro-organisms	EC50	OECD 209	> 100 mg/l		Activated sludge			Literature study

alkanes, C14-17, chloro

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	Equivalent to OECD 203	> 5000 mg/l	96 h	Alburnus alburnus	Static system	Brackish water	Experimental value; Nominal concentration
Acute toxicity crustacea	EC50	OECD 202	0.006 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; GLP
Toxicity algae and other aquatic plants	NOEC	OECD 201	0.1 mg/l	96 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; GLP
	ErC50	OECD 201	> 3.2 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; GLP
Long-term toxicity fish	NOEC	Equivalent to OECD 204	> 125 µg/l	14 day(s)	Alburnus alburnus	Semi-static system	Brackish water	Experimental value
Long-term toxicity aquatic crustacea	NOEC	OECD 202	0.01 mg/l	21 day(s)	Daphnia magna	Static system	Fresh water	Experimental value

	Parameter	Method	Value	Duration	Species	Value determination
Toxicity soil macro-organisms	NOEC	OECD 222	900 mg/kg soil dw	56 day(s)	Eisenia fetida	Experimental value
Toxicity soil micro-organisms	NOEC	OECD 216	≥ 400 mg/kg soil dw	28 day(s)	Soil micro-organisms	Experimental value
	EC50	OECD 216	> 400 mg/kg soil dw	28 day(s)	Soil micro-organisms	Experimental value
Toxicity terrestrial plants	NOEC	OECD 208	≥ 5000 mg/l	28 day(s)	Brassica napus	Experimental value
Toxicity birds	LC50	Equivalent to OECD 205	> 24603 mg/kg food	5 day(s)	Phasianus colchicus	Experimental value
	NOEC	Equivalent to OECD 205	24603 mg/kg food	5 day(s)	Phasianus colchicus	Experimental value

Classification is based on the relevant ingredients

#### Conclusion

May cause long lasting harmful effects to aquatic life.

### 12.2. Persistence and degradability

polymethylene polyphenyl isocyanate

Biodegradation water

Method	Value	Duration	Value determination
OECD 302C: Inherent Biodegradability: Modified MITI Test (II)	< 60 %		Experimental value

alkanes, C14-17, chloro

Biodegradation water

Method	Value	Duration	Value determination
OECD 301D: Closed Bottle Test	37 %; GLP	28 day(s)	Experimental value

Biodegradation soil

Method	Value	Duration	Value determination
	51 % - 57 %	36 h	Experimental value

#### Conclusion

Contains non readily biodegradable component(s)

### 12.3. Bioaccumulative potential

Soudal SA Fill & Fix Foam

Log Kow

Method	Remark	Value	Temperature	Value determination
--------	--------	-------	-------------	---------------------

Publication date: 2017-06-02

# Soudal SA Fill & Fix Foam

	Not applicable (mixture)			
--	--------------------------	--	--	--

## polymethylene polyphenyl isocyanate

### BCF fishes

Parameter	Method	Value	Duration	Species	Value determination
BCF		1		Pisces	Literature study

### Log Kow

Method	Remark	Value	Temperature	Value determination
	No data available			

## alkanes, C14-17, chloro

### BCF fishes

Parameter	Method	Value	Duration	Species	Value determination
BCF	OECD 305	6660	35 day(s)	Oncorhynchus mykiss	Experimental value

### Log Kow

Method	Remark	Value	Temperature	Value determination
		5.47 - 8.01		Experimental value
		> 5		

### Conclusion

Contains bioaccumulative component(s)

## 12.4. Mobility in soil

### alkanes, C14-17, chloro

#### (log) Koc

Parameter	Method	Value	Value determination
log Koc		5	Experimental value

### Conclusion

Contains component(s) that adsorb(s) into the soil

Contains component(s) with potential for mobility in the soil

## 12.5. Results of PBT and vPvB assessment

Due to insufficient data no statement can be made whether the component(s) fulfil(s) the criteria of PBT and vPvB according to Annex XIII of Regulation (EC) No 1907/2006.

## 12.6. Other adverse effects

### Soudal SA Fill & Fix Foam

#### Fluorinated greenhouse gases (Regulation (EU) No 517/2014)

None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014)

#### Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

## SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

### 13.1. Waste treatment methods

#### 13.1.1 Provisions relating to waste

##### European Union

Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014.

Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

08 05 01\* (wastes not otherwise specified in 08: waste isocyanates).

16 05 04\* (gases in pressure containers and discarded chemicals: gases in pressure containers (including halons) containing hazardous substances).

Depending on branch of industry and production process, also other waste codes may be applicable.

#### 13.1.2 Disposal methods

Recycle/reuse. Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Specific treatment. Do not discharge into drains or the environment.

#### 13.1.3 Packaging/Container

##### European Union

Waste material code packaging (Directive 2008/98/EC).

15 01 10\* (packaging containing residues of or contaminated by dangerous substances).

## SECTION 14: Transport information

Publication date: 2017-06-02

# Soudal SA Fill & Fix Foam

## Road (ADR)

### 14.1. UN number

UN number	1950
-----------	------

### 14.2. UN proper shipping name

Proper shipping name	Aerosols
----------------------	----------

### 14.3. Transport hazard class(es)

Hazard identification number	
Class	2
Classification code	5F

### 14.4. Packing group

Packing group	
Labels	2.1

### 14.5. Environmental hazards

Environmentally hazardous substance mark	no
--	----

### 14.6. Special precautions for user

Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

## Rail (RID)

### 14.1. UN number

UN number	1950
-----------	------

### 14.2. UN proper shipping name

Proper shipping name	Aerosols
----------------------	----------

### 14.3. Transport hazard class(es)

Hazard identification number	23
Class	2
Classification code	5F

### 14.4. Packing group

Packing group	
Labels	2.1

### 14.5. Environmental hazards

Environmentally hazardous substance mark	no
--	----

### 14.6. Special precautions for user

Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

## Inland waterways (ADN)

### 14.1. UN number

UN number	1950
-----------	------

### 14.2. UN proper shipping name

Proper shipping name	Aerosols
----------------------	----------

### 14.3. Transport hazard class(es)

Class	2
Classification code	5F

### 14.4. Packing group

Packing group	
Labels	2.1

### 14.5. Environmental hazards

Environmentally hazardous substance mark	no
--	----

### 14.6. Special precautions for user

Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625

Publication date: 2017-06-02

# Soudal SA Fill & Fix Foam

Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)
--------------------	--

## Sea (IMDG/IMSBC)

14.1. UN number	UN number	1950
14.2. UN proper shipping name	Proper shipping name	Aerosols
14.3. Transport hazard class(es)	Class	2.1
14.4. Packing group	Packing group	
	Labels	2.1
14.5. Environmental hazards	Marine pollutant	-
	Environmentally hazardous substance mark	no
14.6. Special precautions for user	Special provisions	63
	Special provisions	190
	Special provisions	277
	Special provisions	327
	Special provisions	344
	Special provisions	381
	Special provisions	959
	Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)
14.7. Transport in bulk according to Annex II of Marpol and the IBC Code	Annex II of MARPOL 73/78	Not applicable

## Air (ICAO-TI/IATA-DGR)

14.1. UN number	UN number	1950
14.2. UN proper shipping name	Proper shipping name	Aerosols, flammable
14.3. Transport hazard class(es)	Class	2.1
14.4. Packing group	Packing group	
	Labels	2.1
14.5. Environmental hazards	Environmentally hazardous substance mark	no
14.6. Special precautions for user	Special provisions	A145
	Special provisions	A167
	Special provisions	A802
	Limited quantities: maximum net quantity per packaging	30 kg G

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European legislation:

VOC content Directive 2010/75/EU

VOC content	Remark
18.2 % - 25.5 %	
172 g/l - 241 g/l	

REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

	Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
polymethylene polyphenyl isocyanate alkanes, C14-17, chloro	Liquid substances or mixtures which are regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the	1. Shall not be used in: — ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,

Publication date: 2017-06-02

# Soudal SA Fill & Fix Foam

	<p>criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008:</p> <p>(a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F;</p> <p>(b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10;</p> <p>(c) hazard class 4.1;</p> <p>(d) hazard class 5.1.</p>	<p>— tricks and jokes,</p> <p>— games for one or more participants, or any article intended to be used as such, even with ornamental aspects, 2. Articles not complying with paragraph 1 shall not be placed on the market. 3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they:</p> <p>— can be used as fuel in decorative oil lamps for supply to the general public, and,</p> <p>— present an aspiration hazard and are labelled with R65 or H304, 4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN). 5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met:</p> <p>a) lamp oils, labelled with R65 or H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil — or even sucking the wick of lamps — may lead to life-threatening lung damage";</p> <p>b) grill lighter fluids, labelled with R65 or H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter may lead to life threatening lung damage";</p> <p>c) lamp oils and grill lighters, labelled with R65 or H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010. 6. No later than 1 June 2014, the Commission shall request the European Chemicals Agency to prepare a dossier, in accordance with Article 69 of the present Regulation with a view to ban, if appropriate, grill lighter fluids and fuel for decorative lamps, labelled R65 or H304, intended for supply to the general public. 7. Natural or legal persons placing on the market for the first time lamp oils and grill lighter fluids, labelled with R65 or H304, shall by 1 December 2011, and annually thereafter, provide data on alternatives to lamp oils and grill lighter fluids labelled R65 or H304 to the competent authority in the Member State concerned. Member States shall make those data available to the Commission.'</p>
--	--	--

## National legislation Belgium

Soudal SA Fill & Fix Foam  
No data available

## National legislation The Netherlands

Soudal SA Fill & Fix Foam

Waste identification (the Netherlands)	LWCA (the Netherlands): KGA category 06
Waterbezwaarlijkheid	Z (2)

## National legislation France

Soudal SA Fill & Fix Foam  
No data available

## National legislation Germany

Soudal SA Fill & Fix Foam

WGK	2; Classification water polluting based on the components in compliance with Verwaltungsvorschrift wassergefährdender Stoffe (VwVwS) of 27 July 2005 (Anhang 4)
-----	---

## polymethylene polyphenyl isocyanate

TA-Luft	5.2.5; I
TRGS900 - Risiko der Fruchtschädigung	pMDI (als MDI berechnet); Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden
Sensibilisierende Stoffe	pMDI (als MDI berechnet); Sa; Atemwegssensibilisierende Stoffe
TRGS905 - Krebszeugend	Techn. ("Polymeres") MDI (pMDI) (in Form atembarer Aerosole, A-Fraktion); 2
TRGS905 - Erbgutverändernd	Techn. ("Polymeres") MDI (pMDI) (in Form atembarer Aerosole, A-Fraktion); -
TRGS905 - Fruchtbarkeitsgefährdend	Techn. ("Polymeres") MDI (pMDI) (in Form atembarer Aerosole, A-Fraktion); -
TRGS905 - Fruchtschädigend	Techn. ("Polymeres") MDI (pMDI) (in Form atembarer Aerosole, A-Fraktion); -
Hautresorptive Stoffe	pMDI (als MDI berechnet); H; Hautresorptiv

## alkanes, C14-17, chloro

TA-Luft	5.2.5; I
TRGS900 - Risiko der Fruchtschädigung	Chloralkane, C14-17 (Chlorierte Paraffine C14-17); Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden
Hautresorptive Stoffe	Chloralkane, C14-17 (Chlorierte Paraffine C14-17); H; Hautresorptiv

## National legislation United Kingdom

Soudal SA Fill & Fix Foam  
No data available

## polymethylene polyphenyl isocyanate

Skin Sensitisation	Isocyanates, all (as -NCO) Except methyl isocyanate; Sen
Respiratory sensitisation	Isocyanates, all (as -NCO) Except methyl isocyanate; Sen

Publication date: 2017-06-02

# Soudal SA Fill & Fix Foam

## Other relevant data

Soudal SA Fill & Fix Foam

No data available

polymethylene polyphenyl isocyanate

IARC - classification	3; Polymethylene polyphenyl isocyanate
-----------------------	--

alkanes, C14-17, chloro

IARC - classification	2B; Chlorinated paraffins
-----------------------	---------------------------

## 15.2. Chemical safety assessment

alkanes, C14-17, chloro

A chemical safety assessment has been performed.

## SECTION 16: Other information

Full text of any H-statements referred to under headings 2 and 3:

H220 Extremely flammable gas.  
H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H280 Contains gas under pressure; may explode if heated.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H335 May cause respiratory irritation.  
H351 Suspected of causing cancer.  
H362 May cause harm to breast-fed children.  
H373 May cause damage to organs through prolonged or repeated exposure if inhaled.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.  
H413 May cause long lasting harmful effects to aquatic life.

(\*) INTERNAL CLASSIFICATION BY BIG  
CLP (EU-GHS) Classification, labelling and packaging (Globally Harmonised System in Europe)  
DMEL Derived Minimal Effect Level  
DNEL Derived No Effect Level  
EC50 Effect Concentration 50 %  
ErC50 EC50 in terms of reduction of growth rate  
LC50 Lethal Concentration 50 %  
LD50 Lethal Dose 50 %  
NOAEL No Observed Adverse Effect Level  
NOEC No Observed Effect Concentration  
OECD Organisation for Economic Co-operation and Development  
PBT Persistent, Bioaccumulative & Toxic  
PNEC Predicted No Effect Concentration  
STP Sludge Treatment Process  
vPvB very Persistent & very Bioaccumulative

### M-factor

alkanes, C14-17, chloro	100	Acute	BIG
alkanes, C14-17, chloro	10	Chronic (NRD)	BIG

### Specific concentration limits CLP

polymethylene polyphenyl isocyanate	C ≥ 5 %	Eye Irrit 2;H319	analogous to Annex VI
	C ≥ 5 %	Skin Irrit 2;H315	analogous to Annex VI
	C ≥ 0.1 %	Resp Sens 1;H334	analogous to Annex VI
	C ≥ 5 %	STOT SE 3;H335	analogous to Annex VI

Publication date: 2017-06-02



# Soudal SA Fill & Fix Foam

alkanes, C14-17, chloro	1,0 % ≤ C ≤ 20 %	EUH066	FEICA Position Paper on the classification and labelling of One Component Foam (OCF) containing Mid Chained Chlorinated Paraffin (MCCP) March 7th 2014)
	1,0 % ≤ C ≤ 20 %	Lact. ; H362	FEICA Position Paper on the classification and labelling of One Component Foam (OCF) containing Mid Chained Chlorinated Paraffin (MCCP) March 7th 2014)
	0,25 % ≤ C ≤ 20 %	Aquatic Chron. 4;H413	FEICA Position Paper on the classification and labelling of One Component Foam (OCF) containing Mid Chained Chlorinated Paraffin (MCCP) March 7th 2014)

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Old versions must be destroyed. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet has been elaborated for use within the European Union, Switzerland, Iceland, Norway and Lichtenstein. It may be consulted in other countries, where local legislation with regards to the set-up of safety data sheets will take precedence. It is your obligation to verify and apply such local legislation. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.

Publication date: 2017-06-02